Wireless installation handle

FOR HYDROELITE





Wireless installation handle for HydroElite®





Receiver



Connector P2O3 on Hydroelite 3G-1



Charger/Antenna

Usage

Hydrowares wireless installation handle is intended to control Hydroelite 3G -1 when installing. The system is equipped with dual safety relays and complies to SIL3 IEC 61508 and PLe . The system is also certified according to CSA in the US and Canada.

The product comes with the following parts

- Remote control 1.
- 2. Shoulder strap for remote control
- 3. Receiver with connection cable with connector for Hydroelite 3G-1. Including magnetic feet.
- 4. Antenna to the receiver
- 5. Charger
- 6. Wall bracket for charger

Article no.	1200038
Frequency	433 MHz , 69 channels
Mod.type	FM-Modulation, narrow band
Code comb	4.200.000.000
Radio type	Low IF topology
Output	10 mW (by 50 ohm)
No. of batteries	1
Battery	Re-chargeable
Type of batteries	Li-ion
Operating time	30 h
Weight	295 g / ~ 0.6 lb
Dimensions	76x160x37 mm/~ 3x6.3x1.5 in
Protection	IP66
Temperature	-20° till +55° C / -4 to +130 F
Safety level	SIL3, PLe
On/off switch	Yes
Range	Approx. 400 m

Hydroware (UK) Ltd

21 St Thomas Street Bristol BS1 6JS United Kingdom +44 (0)7500 009057 www.hydroware.co.uk

Hydroware AB Fabriksgatan 13 Box 66 SE-342 32 Alvesta Sweden Tel +46 (0)472 451 00 www.hydroware.se

